



# SOUND ASSOCIATES, INC.



## SA1532P - Multi-Channel Infrared Stereo Receiver user selectable to 2.3 MHz, 2.8 MHz or Stereo (2.3 MHz and 2.8 MHz)

The Sound Associates wireless pendant-style receiver is designed for professional applications to be used with the SA1520NIL Neck Induction Loop and other audio devices with a 3.5 mm plug. It is equipped with a sophisticated receiving circuitry with multiple receiving diodes to increase sensitivity.

The SA1532P is switchable to receive a frequency modulation of 2.3 MHz or 2.8 MHz or stereo (2.3 MHz and 2.8 MHz) and is both easy and comfortable to wear, using either the neck lanyard or lapel clip.

Powered by a light weight lithium polymer rechargeable battery, it is designed with a new industrial-strength chassis for added durability in commercial applications. Its advanced mechanical design ensures years of trouble-free use.

## FEATURES

- Automatically powers on when 3.5 mm plug is inserted
- Lithium Polymer battery for quick recharging.
- Automatic mute when no infrared signal is present
- Multiple receiving diodes and IR transparent case for wider scope of coverage and greater sensitivity.
- Soft neck lanyard and spring lapel clip.
- Slide volume and channel selection for simple operation.
- Two selectable channels for multi-language interpretation or stereo.
- Rechargeable battery that charges in the receiver for ease of distribution.
- Full one-year warranty.

Make your wireless infrared listening system T-Coil compatible



*SA1520NIL Neck Induction Loop sold separately*

424 West 45th Street, New York, NY 10036 TEL: 212-757-5679

**TOLL FREE 888-772-SOUND** (888-772-7686)

[www.soundassociates.com](http://www.soundassociates.com)



# SOUND ASSOCIATES, INC.



All Sound Associates pendant receivers include (1) rechargeable SA1505 battery and neck lanyard. Neck Induction Loop sold separately.

## Technical Specification:

	<b>SA1532</b>
Modulation .....	Ch. 1: 2.3 MHz Ch. 2: 2.8 MHz Ch. S: Stereo (L: 2.3 MHz; R: 2.8 MHz)
Infrared Wavelength .....	880 - 1200 nm
Output .....	116 dB SPL @ 1 KhZ (with SA600E earpiece)
Frequency Response .....	200 Hz - 6 kHz (-3 dB)
Operation time (fully charged battery) .....	Approx 6 hours
Charging Time .....	Approx 4 hours
Battery .....	3.7 V Lithium Polymer 150 mAh
Dimension .....	2.25" x 3.0" x 0.75" deep
Weight .....	3.2 oz (with battery)
Audio Output .....	3.5 mm jack
Channel Indicator .....	Blue LED (top)

## Accessories:

SA1505	Rechargeable lithium polymer battery (included)	SA1520NIL	Neck Induction Loop
SA1930	Smart Charger: 10 position battery charger	SA1905-3	Smart Charger: 3 position battery charger

## Warranty

The SA1532P pendant receiver and the SA1505 rechargeable battery are covered by a full one-year warranty from the original date of purchase, against defects in workmanship or materials. If either component fails due to defects in craftsmanship or materials, we will repair or replace the component without charge. The factory warranty does not cover malfunctions due to abuse or operation other than specified.